# G-Series Lift Tables

LIFT PRODUCTS, INC.

## Light Duty Industrial Lift Tables



2,000 lb. Capacity



3,000 lb. Capacity

The G-Series Lift Tables have been designed as an economical solution for light duty industrial applications. Available with 2,000 lb. and 3000 lb. capacities, the G-Series table can improve productivity and reduce injuries by placing loads at an ergonomic work height. The heavy duty 1.7 HP lift motor allows up to 12 full lifts per hour on average, with a competitive lift speed and runs on a 115 volt input 15 amp circuit. Available in 4 models, the G-Series has the right table for many applications. The G-Series tables are stock items and can usually ship in 24 hours.

The 3 G-Series Lift Tables offer a 3,000 lb. capacity. This lift table features 2 lift cylinders for increased capacity and has the same standard features as the 2 G models.

The G-Series tables are available with several options, foot controls, fork pockets, casters and push handles. Contact factory for more information.

Model	Capacity	Platform	Base Size	Low	Raised	Lift	Lowered	Motor	Wt
		Size		Height	Height	Speed	Speed Empty		
2G-2849	2,000 lb.	28" x 49"	24.75"x 46"	8"	40"	18.5 sec	17.6 sec	1.7 HP	400 lb.
2G-3849	2,000 lb.	38" x 49"	24.75"x 46"	8"	40"	18.5 sec	17.6 sec	1.7 HP	425 lb.
3G-3049	3,000 lb.	30" x 49"	29.25"x 45"	8"	40"	28 sec	33 sec	1.7 HP	530 lb.
3G-3849	3,000 lb.	38" x 49"	29.25"x 45"	8"	40"	28 sec	33 sec	1.7 HP	550 lb.

Note: Capacity is based on evenly distributed loads. Offset loads will reduce capacity by 50% or more depending on placement and size. Contact factory for requirements.

#### Lift Products, Inc.

P.O. BOX 349

Elm Grove, WI 53122-0349

Toll Free: 877.LIFTPRO (877.543.8776) Phone: 262.521.5720 Fax: 262.521.5725

lpi@liftproducts.com www.liftproducts.com

### Standard Features

- Upper Platform Full Perimeter Safety Bar which prevents descent upon contact with an obstruction.
- Low Tension (24v) control box with up and down buttons. In addition the G-Series includes an electric circuit reset button in case safety perimeter bar is activated.
- Upper limit switch shuts motor off at full height extension reducing wear on lift cylinder and motor.
- Single acting lift cylinder with flow control to prevent fast lowering in case of hose burst.
- Lifetime lubricated bearings on lift arms.
- 1.7 Hp 115 volt motor with low amp draw and reliable performance.
- Runs on a standard 15 amp circuit.

#### The Full Perimeter Safety Bar


The full perimeter safety bar stops the table from lowering if it comes in contact with an obstruction. This feature improves safety when the table is used next to machinery, packing tables, work benches or other items when the table could cause entrapment while lowering. To reactivate the table the operator must reset the button on the control box.

#### **Built In Maintenance Bar**

The table includes built-in Flip Down Bars on each side of the outer scissors arms. These bars are to be flipped down while performing maintenance or inspection.

#### **Exclusive 1.7 Hp Lift Motor**

This intentionally oversized motor performs at a competitive lift speed with low amp draw. The high torque low RPM (1,700) lift motor is ETL-Rated. This 1.7 Hp motor is energy efficient, can run on a standard 15 amp circuit, and also features quiet operation.



Full Perimeter Safety Bar



Built-In Maintenance Bar



Exclusive 1.7 Hp Lift Motor



#### Lift Products, Inc.

P.O. BOX 349

Elm Grove, WI 53122-0349

Toll Free: 877.LIFTPRO (877.543.8776) Phone: 262.521.5720 Fax: 262.521.5725

lpi@liftproducts.com www.liftproducts.com